

The Alan Turing Institute

Aircraft as Weather Sensors

ONLINE REFINEMENT OF WEATHER FORECASTS FOR USE IN TACTICAL AIR TRAFFIC CONTROL



Jan Povala + Project Bluebird



Image source: https://flic.kr/p/nf7rhQ

Project Bluebird: Modernising UK airspace

- Deliver the first AI system to work with air traffic controllers and control a section of airspace in live trials.
- Increase the throughput, and help the UK aviation industry achieve net zero carbon emissions.
- The fundamental block of the project is a high-fidelity probabilistic **Digital Twin**.

Digital Twin of UK Airspace

- A digital model of the airspace allows for:
 - Better understanding of the physical system.
 - Testing what-if scenarios particularly useful for testing the increase in throughput.



Trajectory Prediction

- Trajectory prediction for a given clearance/ instruction is the fundamental component of the digital twin.
- Several sources of uncertainty:
 - Unknown mass
 - Unknown controller intent
 - Pilot intent/airline procedures
 - Meteorological conditions





Wind

- A result of pressure gradient force and Coriolis force.
- Flow is almost completely horizontal.
- Impacts comfort/safety, time schedules, fuel consumption.
- Necessary for high-fidelity simulations of trajectories.





Objective

- Incorporate a representation of wind into the Digital Twin.
- Leverage different sources of information: combine wind forecasts from weather agencies and the measurements of wind from airborne aircraft.
 Note: we are not looking to capture gusts that last
 - a few seconds.

Wind: bivariate field

- The airspace is a 3D domain.
- Discretise airspace spatially (latitude, longitude) and vertically (pressure levels).
- The wind at each of the discretisation points is represented by vector components *u*, *v*.



Wind Measurements

- Compute true airspeed (TAS) vector from indicated airspeed, heading, and flight level (necessary for converting indicated airspeed to true airspeed).
- The ground velocity vector given by ground speed and the track angle.
- Wind vector simply follows as $\vec{v}_{wind} = \vec{v}_{ground} \vec{v}_{TAS}$
- We discard measurements from manoeuvring aircraft (climbing, turning) and with more than 45deg crosswind.



Data Assimilation

- Weather forecasts from NOAA* are issued every 6 hours for times in the future at 6-hour multiples.
- In between, we can derive measurements of wind velocity from airborne aircraft.
- Combine wind forecasts from wind measurements from the aircraft in an online manner \rightarrow **filtering problem**.
- Extensive literature on this subject: Kalman Filters.

*could be other agencies, e.g., MET Office.

Filtering Formulation

$$\boldsymbol{\psi}_{k} = \boldsymbol{M}_{k} \boldsymbol{\psi}_{k-1} + \boldsymbol{w}_{k}, \qquad \boldsymbol{w}_{k} \sim \mathcal{N}_{n} \left(\boldsymbol{0}, \boldsymbol{Q}_{k} \right),$$

$$\boldsymbol{y}_{k} = \boldsymbol{H}_{k} \boldsymbol{\psi}_{k} + \boldsymbol{v}_{k}, \qquad \boldsymbol{v}_{k} \sim \mathcal{N}_{m_{k}} \left(\boldsymbol{0}, \boldsymbol{R}_{k} \right),$$

- M_k is the state transition operator,
- w_k is the state transition innovation term, a **random field**,
- H_k is the observation operator mapping from state to observations at step k,
- v_k is the measurement noise,
- \boldsymbol{Q}_k is the covariance matrix for the innovation term,
- \boldsymbol{R}_k is the covariance matrix for the measurement noise (assumed diagonal).

State Update

- Without the knowledge of the physical process (requiring a climate model), we leverage the forecasts for the time before step k (T0), and after step k (T0 + 6), and interpolate them to obtain the expected wind at step k, based on the forecasts: $\psi_k = w \times \psi_{k-1} + (1 - w) \times f(k, \psi^*_{prev}, \psi^*_{next}) + w_k$.
- This approach guides the state update, with weight *w* determining the influence of the previous state, and the expected state based on forecasts.



State Update continued

- Covariance matrix Q_k is a covariance matrix generated using separable covariance function $k([x_1, y_1, z_1], [x_2, y_2, z_2]) = k_{xy}([x_1, y_1], [x_2, y_2])k_z(z_1, z_2)$.
- This allows for Kronecker factorisation: $Q_k = K_{xy} \otimes K_z$
- Linear algebra cost significantly reduced, e.g., Cholesky factorisation cost goes down from $\mathcal{O}(n^3)$ to $\mathcal{O}(n^{3/2})$.

Implementation

- Due to high dimensionality of the state space, we employ **Ensemble Kalman** filter \rightarrow the distribution at step k is given by an ensemble of members.
- Efficient Maximum Likelihood estimation of the parameters of the filter: lateral and vertical length scales of innovation term, and its amplitude.
- Auto-differentiation in JAX to find optimal parameters for the filtering scheme.
- Assuming separable covariance structure \rightarrow efficient factorisation using **Kronecker product**.

Experiments



Density of radar blips in a 6H window in SE England

Wind Field Updates



Evaluation

- Ground truth of wind is sparse:
 - Reanalysis data from weather agencies comes at hourly resolution and is averaged.
 - Radiosonde weather balloon measurements are sparse spatially.
 - End-to-end validation with a simulator and comparing against the radar: we simulate real-life instructions from the controllers and compare to the radar data.

End-to-end Simulation: route-following



Fig: Trajectories and the corresponding error: no-wind (orange), interpolated wind (purple), filtered wind (red)

Using filtered wind reduced the along-the track distance error, compared to the wind given by interpolating two forecasts (which are 6hr apart).

End-to-end Simulation: on-heading aircraft



Fig: Trajectories and the corresponding error: no-wind (orange), interpolated wind (purple), filtered wind (red)

- The error gets more pronounced for on-heading aircraft.
- Filtering reduces along-the-track error.

End-to-end Simulation: a bad case



Fig: Trajectories and the corresponding error: no-wind (orange), interpolated wind (purple), filtered wind (red)

End-to-end Simulation: short segment



No-wind simulation





Error: forecast interpolation (purple), filtered wind (red), no-wind (orange)

Filtered-wind simulation

State update sensitivity



Fig: along-the-track error: no-wind (orange), interpolated wind (purple), filtered wind (red)

Conclusions

- Not including wind conditions in the digital twin can result in up to 10nm in along-the-track distance for a 20-min flight.
- Filtering methods are a natural choice for assimilating wind measurements from the aircraft.
- Using random fields allows for enforcing the smooth changes in wind velocity.
- The state transition step leverages forecasts to guide the filtering distribution.
- By assuming separability of the horizontal dimension from the vertical dimension in the innovation term, this method scales up to 1000's of discretisation points.
- Hard to verify usefulness of the algorithm as ground truth data measurements are sparse.
- We have employed end-to-end simulation replicating aircraft trajectories and compared to radar data, with promising results.

Next steps

- A suite of experiments covering more aircraft.
- Assessing the covariance separability assumption.
- Assessing the stationarity assumption of the covariance function (the covariance is only dependent on distances, rather than locations).



Questions?